

PROLOGS

1/8 OFFROAD BUGGY

Setup Sheet / Setup Blatt / Feuille de réglage

Date

Driver

Track

Engine Gasket Plug Muffler Fuel

Clutch bell 13T 14T Other T Spur gear 44T Other T Shoes 3 4 Spring

Diff Front: LSD Oil #50000 Center: LSD Oil #50000 Rear: LSD Oil #30000

Front Suspension

Tire

Camber

C-Hub 20' 22 deg.

Ride Height

Rebound Stop

Inner #

Front Toe angle

Caster angle

Steering Slider A B

Anti-roll bar mm 2.5 mm

Front Shock

Oil #

Piston

Spring

Spacer

Length

Rear Suspension

Tire

Camber

Ride Height

Rebound Stop

Inner #

Rear Toe angle

Wing Position

Anti-roll bar mm 2.8 mm

Rear Shock

Oil #

Piston

Spring

Spacer

Length

Notes

- #R26027 CNC Shock Tower front (2nd upper inner hole)
- #R26028 CNC Shock Tower rear (2nd center inner hole)
- no front anti-roll bar for maximum grip

Result	Position	Laps	Time	Fastest Lap
Run				lap
Qualfier	3			lap
				lap
				lap
Main #	2			lap

ROBTRONIC
POWER FOR WINNERS